# MST410






| | |
|---|---|
| **GENERAL INFORMATION** | |
| **pitch** | - |
| **Height** | 26.3 mm |
| **Depth** | 44.5 mm |
| **Dimensional class** | Media |
| **Wire section** | 4.0 mm² / 12 AWG |
| **Clamp opening size** | 3.1 x 3.9 mm |
| **Wire stripping** | max 10 mm |
| **Operating temperature** | -40 ÷ +130 °C |
| **ELECTRICAL CHARACTERISTICS** | |
| **Current** | 10 A |
| **Voltage** | 450 V |
| **impulse voltage** | 2.5 kV |
| **MECHANICAL CHARACTERISTICS** | |
| **Screw** | M3 |
| **Recommended torque** | 0.5÷0.55 Nm / 404÷444.4 in.lbs |
| **APPROVALS DATA** | |

| | EN 60998-1 | | UL 1059 |
|---|---|---|---|
| **Current** | 10 A | - | 25 A factory / 20 A field |
| **Voltage** | 450 V | - | 300 V |
| **Wire section** | 4.0 mm² | - | 12 AWG |
| **Torque** | 0.5 Nm | - | 4.5 Nm |
| **FILE** | EQ204 | - | E178356 |

| | |
|---|---|
| **MATERIALS** | |
| **Housing** | PA - UL 94 V0 |

| | |
|---|---|
| **Screw** | Galvanized steel |
| **Clamp** | Nickel-plated copper alloy |
| **Terminal** | Nickel-plated copper alloy |
| **SCIP Number** | 7ad67f7c-c98b-4a38-af9d-85b3fe2caf8c |

## COLOURS

**Standard**

**On request**