
MVS15_-5-H







GENERAL INFORMATION

pitch Height Depth

Dimensional class Wire section

Clamp opening size

Wire stripping

Operating temperature **ELECTRICAL CHARACTERISTICS**

Current Voltage impulse voltage

MECHANICAL CHARACTERISTICS


Current

Voltage

Wire section

Recommended torque

APPROVALS DATA





5 mm 13.2 mm 8.9 mm Bassa 1.5 mm² / 16 AWG 2.5 x 3.1 mm max 7 mm -40 ÷ +130 °C

> 17.5 A 450 V 2.5 kV

m3 0.5÷0.55 Nm / 4.5÷4.9 in.lbs





EN 60998-1 17.5 A 450 V 1.5 mm²

CA02.00598

Torque 2.5 Nm **FILE**

UL 1059

17.5 A factory / 10 A field

300 V **16 AWG** 4.5 Lb-in E178356

MATERIALS

Housing Screw Clamp Terminal SCIP Number COLOURS PA - UL 94 V0 Galvanized steel Nickel-plated copper alloy Tin-plated copper alloy 713ad43e-8dff-4607-9cfa-843d4a730153

OLOUKS











On request





POLES

I OLLO	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	

NAME MVS152-5-H MVS153-5-H MVS154-5-H MVS155-5-H MVS156-5-H MVS157-5-H MVS158-5-H MVS159-5-H MVS1510-5-H MVS1511-5-H

File available
File not available for this product
File not available for this product