


SHS__-5,08-L



SHSxx-5,08-L



GENERAL INFORMATION

pitch	5,08 mm
Height	10.8 mm
Depth	13.5 mm
Dimensional class	Media
Wire section	1.5 mm ² / 16 AWG
Clamp opening size	-
Wire stripping	max 6 mm
Operating temperature	-40 ÷ +130 °C

ELECTRICAL CHARACTERISTICS

Current	10 A
Voltage	250 V
Test Voltage	4 kVrms/60s

MECHANICAL CHARACTERISTICS

Screw	M2.5
Recommended torque	0.4÷0.44 Nm / 3.6÷3.9 in.lbs

APPROVALS DATA



Current	-	EN 61984 12 A	UL 1059 10 A factory / 10 A field
Voltage	-	200 V	300 V
Wire section	-	0.2÷2.5 mm ²	16 ÷ 30 AWG
Torque	-	0.4 Nm	3.5 Lb-in
FILE	-	40053107	E178356

MATERIALS

Housing	PA - UL 94 V0
Screw	Galvanized steel
Clamp	Nickel-plated copper alloy
Terminal	Copper alloy
SCIP Number	f59fce50-2030-4a8c-a1d5-32dbe6d47a1f

COLOURS

Standard



On request



POLES

- 02
- 03
- 04
- 05

NAME

- SHS02-5,08-L
- SHS03-5,08-L
- SHS04-5,08-L
- SHS05-5,08-L

3D FILE

- File not available for this product
- File not available for this product
- File not available for this product
- File not available for this product