

# SF\_\_-15,24-P



## GENERAL INFORMATION

pitch	15,24 mm
Height	15.5 mm
Depth	19.2 mm
Dimensional class	Media
Wire section	2.5 mm <sup>2</sup> / 14 AWG
Clamp opening size	2.8 x 2.9 mm
Wire stripping	max 8 mm
Operating temperature	-40 ÷ +130 °C

## ELECTRICAL CHARACTERISTICS

Current	16 A
Voltage	1000 V
Test Voltage	6 kVrms/60s

## MECHANICAL CHARACTERISTICS

Screw	M3
Recommended torque	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

## APPROVALS DATA



Current	-	-	<b>UL 1059</b>
Voltage	-	-	22 A factory / 20 A field
Wire section	-	-	600 V
Torque	-	-	12 ÷ 30 AWG
FILE	-	-	4.5 Lb-in
			E178356

## MATERIALS

Housing	PA - UL 94 V0
Screw	Galvanized steel
Clamp	Nickel-plated copper alloy
Terminal	Nickel-plated copper alloy
SCIP Number	e27c55ac-423d-4d46-808e-20cdb05c39b8

## COLOURS

Standard

On request



**POLES**

02  
03  
04  
05  
06  
07  
08

**NAME**

SF02-15,24-P  
SF03-15,24-P  
SF04-15,24-P  
SF05-15,24-P  
SF06-15,24-P  
SF07-15,24-P  
SF08-15,24-P

**3D FILE**

File not available for this product  
File not available for this product  
File not available for this product  
File not available for this product  
File not available for this product  
File not available for this product  
File not available for this product